## MATERIALS CONTROL FOR AEROSPACE APPLICATIONS

Michael Ferguson: United Space Alliance, LLC.

The distant future of mankind and the ultimate survivability of the human race, as it is known today, will depend on mans ability to break earthly bonds and establish new territorial positions throughout the universe. Man must therefore be positioned to not only travel to, but also, to readily adapt to numerous and varying environments. For this mass migration across the galaxies nothing is as import to the human race as is NASA's future missions into Low Earth Orbit (LEO), to the These missions will form the building blocks to moon, and/or Mars. From these missions, NASA will develop the eternity for mankind. foundations for these building blocks based on sound engineering and scientific principles, both known and yet to be discovered. integrity of the program will lead to development, tracking and control of the most basic elements of hardware production: development and control of applications of space flight materials.

for design purposes involves material Choosing the right governmental regulations associated with as considerations, such manufacturing operations, both safety of usage and of manufacturing, general material usage requirements, material longevity and performance requirements, material interfacing compatibility and material usage performance is subject to environmental Material environments. considerations in as much as a given material may perform exceptionally well at standard temperatures and pressures while performing poorly These concerns may be found true for under non-standard conditions. materials relative to the extreme temperatures and vacuum gradients of The only way to assure that flight worthy high altitude usage. materials are used in design is through testing. However, as with all testing, it requires both time on schedule and cost to the operation.

One alternative to this high cost testing approach is to rely on a materials control system established by NASA. The NASA community relies on the MAPTIS materials control system founded at MSFC and supported by the other NASA Centers. This system is a data bank of all materials used in space flight operations. These materials are rated for several characteristics that are common concerns in high altitude or deep space usage: Odor, off gassing, material fluid compatibility, toxicity, corrosion susceptibility, stress corrosion susceptibility, etc.

All future space operations will require that consideration be given to the use of materials in both low earth orbit and/or deep space operations relative to their ability to contaminate the immediate controlled environment of a vehicle, station or orbital/operational platform. For example, many materials off gas or out gas in low pressure applications; this can lead to nauseating odors or deadly contaminates being released from materials to circulate though out the contained habitable environment.

American Institute of Aeronautics and Astronautics

Copyright © 2005 by United Space Alliance, LLC. Published by the American Institute of Aeronautics and Astronautics, Inc. with permission. These materials are sponsored by the National Aeronautics and Space Administration under Contract NAS9-20000. The U.S. Government retains a paid-up, nonexclusive, irrevocable worldwide license in such materials to reproduce, prepare derivative works, distribute copies to the public, and perform publicly and display publicly, by or on behalf of the U.S. Government. All other rights are reserved by the copyright owner.

Also, many materials are subject to giving off toxic fumes if heated beyond application limits; this issue of flammability routinely occurs with the usage of electronic wiring, wiring assemblies and connectors and the like when high resistance joints cause the generation of heat beyond design limits. Similar types of contamination or adverse reactions can occur with the usage of interfacing of materials that are not compatible with each other. Materials used for structural applications may become brittle, or malleable, depending on the exposure limit extremes. Materials studies dealing with long-term radiation exposure of materials in space operations are still in their relative infancy.

associated properties used in space materials and operations, where contained, controlled and habitable environments are required, must be thoroughly understood and controlled down to the materials control lies Ultimately, piece part level. Engineering has to clearly and concisely define specific engineering. These engineering specifications materials to be used on products. have to be clearly transmitted to vendors and sub vendors to assure that only designed materials are to be used in production operations. The only way to know how materials will respond when used at extreme limits is to test the materials at those limits. Materials testing should be performed during the preliminary stages of design to avoid adverse engineering and schedule impacts.

Initial design goals should rely heavily on materials tested by NASA. The prime contractors are held responsible for assuring only flight worthy materials are actually used in design; consequently, there should be a materials control and monitoring program in place at all Without a monitoring program in place, prime space contractors. materials can slip into design in numerous ways: Off the shelf purchase of hardware (piece parts or assemblies) particularly related to modern commercial electronics; also, in this day and age, obsolete spec control is a huge issue relative to exact identification materials and avoiding intentional or unintentional material substitution at some remote level of vendor control. Ideally, only materials that perform acceptability when tested by NASA should be used for space flight design.